

PPNG 6 - 68 HE - Nitrogen generator with pressure swing adsorption technology

Features & Benefits

- ▶ Advanced energy saving control
 - Reduced air consumption at low nitrogen demand
 - Also compensates for altering ambient conditions and purity settings
 - No compressed air use when no nitrogen is consumed
- ▶ Outstanding air factors thanks to back-flow pressurization
- ▶ High-quality, high-efficient Carbon Molecular Sieves selected for the right application
- ▶ Guaranteed purity
 - Automatically regulates to the requested nitrogen pressure and purity
 - Zirconia sensors for reliable purity measurement
- ▶ Designed & tested for cyclic load
- ▶ Optimal control and monitoring thanks to Purelogic™ Controller
 - Self-protective monitoring of the feed air quality
 - Feed-air blow-off in case of contamination
 - Nitrogen flow, purity and pressure measured and controlled
 - Automatic start-up



General Specifications

- ▶ Pressure Swing Adsorption (PSA) nitrogen generators - extruded profile design
- ▶ Nitrogen purity achievable:
95% - 99.9% (PCT Variant) & 99.95%-
99.999% (PPM variant)
- ▶ Inlet pressure range: 4-13 barg /60-189 psig
- ▶ Inlet temperature range: 5-60°C/41-140°F
- ▶ Required inlet air quality:
1-4-1 according to ISO 8573-1:2010
- ▶ Power supply: 115-230VAC/50-60Hz

Options



Wooden packaging



The PPNG6-68HE series is Pneumatech's premium on-site nitrogen solution for low to medium flows, with best-in-class performance and the most complete scope of supply.

The generator has outstanding air factors at full load thanks to the use of highly efficient Carbon Molecular Sieves (CMS) and back-flow pressurization.

The air consumption is also optimized at reduced nitrogen flow or pressure demands, thanks to the advanced energy

saving algorithm, which automatically adjusts the cycle times of the generator.

The control and monitoring capabilities of the PPNG6-68 HE are truly impressive. Purity is guaranteed at all times by opening the consumer valve only at the requested purity level and flushing nitrogen when purity is not reached. Feed air quality is controlled by monitoring temperature, pressure and PDP. The feed air is blown off in case of contamination. All risks of possible CMS damage are eliminated thanks to the automatic start-up feature.

Technical specifications for PPNG 6 - PPNG 68 HE

Specifications	Units	Vari-ant	Product→ Purity ↓	PPNG 6 HE	PPNG 7 HE	PPNG 9 HE	PPNG 12 HE	PPNG 15 HE	PPNG 18 HE	PPNG 22 HE	PPNG 28 HE	PPNG 30 HE	PPNG 37 HE	PPNG 41 HE	PPNG 50 HE	PPNG 63 HE	PPNG 68 HE
Nominal free nitrogen delivery ⁽¹⁾	m ³ /hr	PCT (%)	95	18.4	23.4	28.8	36.4	46.8	57.2	70.2	86.0	93.6	114.8	128.9	157.7	NA	NA
		PPM (%)	99.9	5.8	7.2	9.0	11.5	14.8	18.0	22.0	26.6	29.2	35.6	40.7	49.7	61.9	66.6
		PPM (%)	99.999	1.9	2.5	2.9	4.0	5.0	6.1	7.9	9.7	10.4	13.0	15.8	19.4	22.7	25.9
Nominal air consumption	m ³ /hr	PCT (%)	95	33.8	43.6	53.3	67.7	87.1	106.6	130.7	159.8	174.2	213.1	243.7	298.1	NA	NA
		PPM (%)	99.9	18.0	23.4	28.4	36.4	46.8	56.9	69.8	85.7	93.2	114.1	135.7	166.0	196.9	221.0
		PPM (%)	99.999	12.2	15.5	19.1	24.1	31.3	38.2	44.3	54.0	59.0	72.4	88.6	108.4	124.2	144.4
Air Factor	-	PCT (%)	95	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.89	2	NA	NA
		99.9	3.19	3.19	3.19	3.19	3.19	3.19	3.19	3.19	3.19	3.19	3.19	3.33	3.33	3.18	3.33
		PPM (%)	99.999	6.3	6.3	6.3	6.3	6.3	6.3	5.6	5.6	5.6	5.6	5.6	5.5	5.6	5.6
Pressure dewpoint outlet	°C /°F			-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40
Maximum pressure drop		PCT (%)	95	0.4	0.4	0.4	0.5	0.5	0.5	0.6	0.6	0.6	0.6	0.6	0.9	0.9	NA
		99.9	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.5	0.5	0.6	0.6
		PCT (%)	99.999	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.3	0.3	0.3
Length	mm		775	775	775	775	775	775	1400	1400	1400	1400	1400	1400	1400	1400	1400
	Inch		31	31	31	31	31	31	55	55	55	55	55	55	55	55	55
Width	mm		840	840	840	840	840	840	840	840	840	840	840	840	840	840	970
	Inch		33	33	33	33	33	33	33	33	33	33	33	33	33	33	38
Height	mm		2015	2015	2015	2015	2015	2015	2015	2015	2015	2015	2015	2015	2015	2015	2015
	Inch		79	79	79	79	79	79	79	79	79	79	79	79	79	79	79
Mass	Kg		264	277	290	326	359	380	619	647	683	736	865	1038	1211	1211	
	Lbs		582	611	639	719	791	838	1365	1426	1506	1623	1907	2288	2670	2670	
Inlet and outlet connections	G/NPT		1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"

1. Flow is measured at Reference Conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 20°C & Air Inlet Quality of ISO 8573-1:2010 class 1-4-1